R.K. Instruments & Controls

TECHNICAL DATASHEET

FLOW & FLAME CONTROL | Office No. 12, 1st Floor, Dhamanwala Service Complex, G.I.D.C., Pandesara, Surat - 394221, Gujarat, India
Phone: +91 9824136145 Email: rkic1976@gmail.com Web: www.rkic.in

Elektrogas VMR2-2 Solenoid Coil

Brand: Elektrogas | Code/Part No.: VMR2-2 | Category: SOLENOID VALVES

Specifications

Model	**VMR2-2**
Connection Size	**Rp3/4**
Power Supply	**230 VAC, 50/60 Hz, 25 VA**
Protection Rating	**IP54**
Maximum Pressure	**200 mbar**
Operating Temperature	**T amb = T fluid, -15°C to +60°C**
Fluid	**NG, LPG (gaseous), Air**
Approvals	**EN 161, Class A - Group 2, CE 0476-22**
Origin	**Made in Italy**



Description

The Elektrogas VMR2-2 is a solenoid coil sized Rp3/4, rated 230 VAC, 50/60 Hz, 25 VA, for use on natural gas, LPG (gaseous), and air service. It is rated to a maximum pressure of 200 mbar, with an IP54 protection rating and an operating temperature range of -15°C to +60°C (ambient equal to fluid temperature). Certified to EN 161, Class A - Group 2, CE marked (0476-22). Manufactured by Elektrogas, Italy.

Typical media compatibility: CNG, PNG, LPG, Air, Nitrogen — confirm against application before installation.