R.K. Instruments & Controls

TECHNICAL DATASHEET

FLOW & FLAME CONTROL | Office No. 12, 1st Floor, Dhamanwala Service Complex, G.I.D.C., Pandesara, Surat - 394221, Gujarat, India
Phone: +91 9824136145 Email: rkic1976@gmail.com Web: www.rkic.in

Elektrogas VMR4 Gas Solenoid Valve (Rp1½")

Brand: Elektrogas | Code/Part No.: VMR4 | Category: SOLENOID VALVES

Specifications

Model	**VMR4, Rp1½"**
Connection Size	**1½" (Rp1½)**
Supply Voltage	**230 VAC, 50/60 Hz**
Power	**20 VA (I max 0.5A)**
Max Pressure	**360 mbar**
Ambient Temp.	**-15°C to +60°C**
Certification	**EN 161 Class A, Group 2, IP54**
Marking	**CE 0694**
Origin	**Made in Italy**



Description

The Elektrogas VMR4 (Rp1½") is a normally-closed automatic-reset gas solenoid valve for shut-off duty on gas lines, with a 1½" connection size, rated 230VAC 50/60Hz with a 20VA coil (0.5A max current) and a maximum working pressure of 360 mbar. Certified to EN 161 Class A, Group 2, IP54, and CE marked (0694), it is rated for an ambient temperature range of -15°C to +60°C. Manufactured by Elektrogas, Italy, for burner, boiler and gas-train safety shut-off applications on 1½" (Rp1½") BSP connections.

Typical media compatibility: CNG, PNG, LPG, Air, Nitrogen — confirm against application before installation.