R.K. Instruments & Controls

TECHNICAL DATASHEET

FLOW & FLAME CONTROL | Office No. 12, 1st Floor, Dhamanwala Service Complex, G.I.D.C., Pandesara, Surat - 394221, Gujarat, India
Phone: +91 9824136145 Email: rkic1976@gmail.com Web: www.rkic.in

Elektrogas VMR/L Solenoid Coil

Brand: Elektrogas | Code/Part No.: 1930.1313 | Category: SOLENOID VALVES

Specifications

Type	**VMR/L 2/3 · 2-3 · 3-3 (360 mbar) / VMR/L 2-5 · 3-5 (500 mbar) / VMR/L 2-60 · 3-60**
Power Supply	**230 VAC, 50/60Hz, 35W**
Class	**Class A**
Protection	**IP54**
Operating Temp	**-15°C to +60°C**
Gas Type	**Air & non-aggressive gases (Family 1-2-3, EN 437)**
Approvals	**CE EN 161, FM, EAC, Australian Gas Mark**
Origin	**Made in Italy**



Description

The Elektrogas VMR/L is the coil/operator head for the VMR series of normally-closed, automatic-reset safety solenoid valves — fast-opening when energised and fast-closing the moment power is cut. It is built for gas and air blocking and control duty on atmospheric and fan-assisted burners, industrial kilns, and other continuous-service (100% ED) gas equipment, and is available across 360 mbar, 500 mbar and 6 bar pressure ratings to match the application. Manufactured by Elektrogas, Italy.

Typical media compatibility: CNG, PNG, LPG, Air, Nitrogen — confirm against application before installation.