R.K. Instruments & Controls

TECHNICAL DATASHEET

FLOW & FLAME CONTROL | Office No. 12, 1st Floor, Dhamanwala Service Complex, G.I.D.C., Pandesara, Surat - 394221, Gujarat, India
Phone: +91 9824136145 Email: rkic1976@gmail.com Web: www.rkic.in

Honeywell Eclipse Spark Ignition Electrode 13047-1

Brand: Honeywell Eclipse | Code/Part No.: 13047-1 / EC13047-1 | Category: IGNITION SPARK ELECTRODES

Specifications

Part Number	**13047-1 / EC13047-1**
Product Type	**Burner Spark Ignition Electrode (Self-Grounding)**
Electrode Base Depth	**54.5 mm (2.17 in.)**
Thread Type / Size	**M14 (14mm x 1.25mm)**
Ignition Voltage	**40 kV minimum**
Operating Temperature	**-100°C to 1350°C**
Burner Compatibility	**Eclipse AH (Airheat) Version 2 burners, Gas Burner Compact, with or without**
Electrode & Wiring Material	**Kanthal A1 (FeCrAl resistance wire), alumina ceramic body**
Manufacturer	**Honeywell Eclipse**



Description

The Honeywell Eclipse 13047-1 is a self-grounding burner spark ignition electrode with a 54.5mm base depth (2.17 in.) and M14 x 1.25mm threaded mounting. Built with a Kanthal A1 electrode and an alumina ceramic body, it is rated for continuous operation from -100°C to 1350°C with a 40kV minimum ignition voltage. It is used on Eclipse AH (Airheat) Version 2 burners and Gas Burner Compact units, with or without flame-rod detection. Manufactured by Honeywell Eclipse.

Typical media compatibility: CNG, PNG, LPG, Air, Nitrogen — confirm against application before installation.