R.K. Instruments & Controls

FLOW & FLAME CONTROL | Office No. 12, 1st Floor, Dhamanwala Service Complex, G.I.D.C., Pandesara, Surat - 394221, Gujarat, India
Phone: +91 9824136145 Email: rkic1976@gmail.com Web: www.rkic.in

Honeywell Elster Quantometer QA16 25 G I Turbine Gas Meter

Brand: Honeywell Elster | Code/Part No.: QA16 25 G I | Category: GAS FLOW METERS

Specifications

Model	**Quantometer QA16 25 G I**
Size and Capacity	**QA16 · Qmax 25 m³/h**
Measuring Principle	**Turbine Wheel (Quantometer QA Series)**
Connection Size	**1" FNPT (DN25)**
Minimum Flow Rate (Qmin)	**2 m³/h**
Maximum Flow Rate (Qmax)	**25 m³/h**
Maximum Operating Pressure	**4 bar**
Temperature Range	**-10°C to +60°C**
Applicable Media	**Natural gas and other non-corrosive gases**
Hazardous Area Rating	**II 2G Ex h IIC T4 Gb**
Index / Readout	**Mechanical roller counter, reading in m³**
Part No.	**8000310657**
Kromschröder Equivalent	**DM 16R25-40**
Kromschröder Part No. (Order No.)	**03200379**
Approvals	**CE 0085, ATEX, IECEx TUR 16.0043X**
Manufacturer	**Elster Instromet (Honeywell Elster)**



Description

The Honeywell Elster Quantometer QA16 25 G I is a turbine-type gas flow meter for industrial, non-fiscal metering, sized DN25 (1" FNPT) with a flow range of 2 to 25 m³/h (Qmin to Qmax). A free-spinning turbine wheel is set in motion by the gas flow, with the number of revolutions proportional to the volume passed, read out via a mechanical roller counter in m³. Rated to a maximum operating pressure of 4 bar, it covers an operating temperature range of -10°C to +60°C, and is ATEX/IECEx certified for use in hazardous areas — hazardous area rating II 2G Ex h IIC T4 Gb, IECEx TUR 16.0043X, CE 0085. Commonly used for in-plant allocation and consumption monitoring on boilers, furnaces and heating systems running on natural gas and other non-corrosive gases. Manufactured by Elster Instromet (Honeywell Elster).

Typical media compatibility: CNG, PNG, LPG, Air, Nitrogen — confirm against application before installation.