R.K. Instruments & Controls

TECHNICAL DATASHEET

FLOW & FLAME CONTROL | Office No. 12, 1st Floor, Dhamanwala Service Complex, G.I.D.C., Pandesara, Surat - 394221, Gujarat, India
Phone: +91 9824136145 Email: rkic1976@gmail.com Web: www.rkic.in

Honeywell Kromschröder KFM 250 MB 100 Pressure Gauge

Brand: Honeywell Kromschröder | Code/Part No.: KFM 250 MB 100 | Category: PRESSURE GAUGES

Specifications

Model	**KFM 250 MB 100**
Type	**Capsule-Element (Diaphragm) Pressure Gauge, Low-Pressure Range**
Measuring Range	**0 – 250 mbar**
Accuracy Class	**KL 1.6 (Class 1.6, per EN 837-3)**
Standard	**EN 837-3 (Capsule-Element Pressure Gauges)**
Dial Size	**100 mm**
Weight	**474 g (1.04 lbs)**
Unit	**mbar**
Case Material	**Stainless steel case**
Process Connection	**G½B, brass, bottom entry, A/F 22 (per Honeywell Kromschröder connection**
Application	**Measurement of low gas and air pressures — gas pressure monitoring,**
Manufacturer	**Honeywell Kromschröder (Elster GmbH, Osnabrück, Germany)**



Description

The Honeywell Kromschröder KFM 250 MB 100 is a mechanical capsule-element (diaphragm) pressure gauge used to measure low gas and air pressures, with a 0–250 mbar range and KL 1.6 (Class 1.6) accuracy per EN 837-3. It has a 100 mm dial with a stainless steel case and a G½B brass bottom-entry connection, and is used for gas pressure monitoring, differential pressure indication, and leak-tightness checks on burner and gas-train systems. Manufactured by Honeywell Kromschröder (Elster GmbH, Osnabrück, Germany).

Typical media compatibility: CNG, PNG, LPG, Air, Nitrogen — confirm against application before installation.