R.K. Instruments & Controls

FLOW & FLAME CONTROL | Office No. 12, 1st Floor, Dhamanwala Service Complex, G.I.D.C., Pandesara, Surat - 394221, Gujarat, India
Phone: +91 9824136145 Email: rkic1976@gmail.com Web: www.rkic.in

Vanaz V7713 / V7715 Safety Relief Valve

Brand: Vanaz | Code/Part No.: V7713 / V7715 | Category: SAFETY RELIEF VALVES

Specifications

Type	**V7713 (½" size) / V7715 (¾" size)**
Connection	**V7713 – ½" | V7715 – ¾" (BSP Internal)**
Gas	**CNG, LPG, CO■, Nitrogen, Argon**
Set Pressure Range	**20 – 200 Kg/cm²**
Seat Type	**Metal-to-metal seat**
Body Material	**Forged brass body**
Manufacturer	**Vanaz Engineers Ltd, Pune**



Description

The Vanaz V7713 (½" size) and V7715 (¾" size) are spring-loaded safety relief valves, identical in specification and differing only in end-connection size. Both stay closed during normal operation and automatically open to vent gas once line pressure rises to the preset limit, closing again once pressure drops back below the set point. Fitted with a metal-to-metal seat, they are built for high-pressure applications with a 20–200 kg/cm² set-pressure range and are suitable for CNG, LPG, CO■, nitrogen and argon service, protecting pressure-reducing systems, gas trains and pipelines from overpressure. Manufactured by Vanaz Engineers Ltd, Pune.

Typical media compatibility: CNG, PNG, LPG, Air, Nitrogen — confirm against application before installation.